



## CICS JS/Server Content Details

URL (key)	DDName	Count	Detail ( SubType / Length / Content)
/USR/image1.jpg	USRFILE	1	D 6 IMAGE1
/USR/image2.jpg	USRFILE	1	D 6 IMAGE2
/USR/image3.jpg	USRFILE	1	D 6 IMAGE3
/USR/jqtools.js	USRFILE	1	D 7 JQTOOLS

Above: three image files described by CICS Document Templates: **IMAGE1**; **IMAGE2** and **IMAGE3**.  
Also, the **jqtools.js** artifact is described by CICS Document Template called **JQTOOLS**.

Below: Application **USR/test994.html** can be seen in its entirety. Freeform text is extensively used and reference to the bespoke content artifacts can be seen (for example **USR/jqtools.js**). In-built system symbols are used also. Part of the web page constructed by this application is built by the CICS program called **JQT0010H**.

/USR/test994.html	USRFILE	6	F	126	<pre> &lt;html&gt; &lt;head&gt; &lt;title&gt; jQuery Tools - Mouseover to switch tabs &lt;/title&gt; &lt;script src="&amp;MF3prf;/USR/jqtools.js"&gt; </pre>
			F	13	<pre> &lt;/script&gt; </pre>
			F	692	<pre> &lt;style type="text/css"&gt; #products img { margin:0 20px 10px 0; cursor:pointer; } .description { background-color:#edecbc; border:1px solid #999; width:500px; min-height:140px; display:none; margin-top:17px; -moz-border-radius:4px; padding:0 20px; } .description .arrow { width:34px; height:34px; background:transparent url(yellow.png) repeat scroll 0 -68px; margin-top:-28px; margin-left:36px; font-size:1px; position:relative; } #commercial .arrow { </pre>

```
        margin-left:210px;
    }
    #multidomain .arrow {
        margin-left:450px;
    }
</style>
```

F

219

```
</head>
<body>
<div id="products">



</div>
```

P

8:JQT0010H

F

148

```
<script>
    $(function() {
        $("#products").tabs("div.description", {event:'mouseover'});
    });
</script>
</body>
</html>
```